24 GAGE STEEL RTA TOOL CABINET
INSTALL INSTRUCTIONS

NEWAGE PRODUCTS INC.

READ THIS FIRST BEFORE UNPACKING CABINET

ALL CABINETS MUST BE MOUNTED TO STUDS ON A SECURE WALL, AS PER THESE INSTRUCTIONS. FAILURE TO DO SO MAY RESULT IN SERIOUS INJURY AND VOIDS PRODUCT WARRANTY AND MANUFACTURER'S LIABILITY.

WARNING:
DO NOT OVERLOAD CABINETS! CABINETS ARE DESIGNED TO CARRY THE FOLLOWING MAXIMUM WEIGHT CAPACITIES:

Cabinet	Shelf Weight Capacity (lbs)	Overall Weight Capacity
Locker	50	200
Wall	40	80
Base	50	150
Tool	30	150

PARTS AND HARDWARE SUPPLIED WITH BASE CABINET:

QTY	ITEM	IMAGE
1	Locking Rod	
47	M5 Frame Screw	
47	M5 Frame Nut	
4	Adjustable Leg	
16	M8 Leg Screws	
16	M8 Leg Screw Nut	
18	M8 Large Washer	
16	Lock Washers	
2	2.5"Wall Screw	
4	5/8"Wood Screw	

DO NOT LEAVE CHILDREN UNATTENDED NEAR CABINETS. WHEN FULLY LOADED, CABINETS ARE HEAVY AND THERE IS A RISK OF CABINETS OR ITEMS TIPPING IF IMPROPERLY OPENED.

CABINET SHOULD BE MOUNTED TO WALL TO AVOID INJURY

WARNING:
EXCESSIVE WEIGHT HAZARD

- Use two or more people to move, assemble or install cabinet or locker.
- Failure to do so can result in back or other injury.

UNPACKING OF THE CABINET:

- Begin by placing the cabinet on a sound level surface.
- Remove all cardboard and foam packaging material.
- Remove clear plastic bag.
- Dispose / recycle all packaging materials.
- Remove and verify all the contents in the box. See "Parts and Hardware Supplied List"

24 GAGE STEEL RTA TOOL CABINET
INSTALL INSTRUCTIONS

NEWAGE PRODUCTS INC.











G Drawer Components











24 GAGE STEEL RTA TOOL CABINET
INSTALL INSTRUCTIONS

NEWAGE PRODUCTS INC.

1. Use the M5 screw and M5 nut to assemble the two back panels.



2. Assemble the left and right side panel with the same screw and nut. D Goes on the outside of A, and C goes on the outside of B.





3. Panel E sits on the outside of A and B, and on the inside of C and D. Do the same for panel F.





4. Flip the cabinet over. Use M8 screw, washer and M8 nut to assemble the adjustable legs on the bottom panel.





5. Turn the cabinet back upwards and assemble drawers. See drawn assembly instructions on next page.





6. To install drawers, line up runners on the side of the drawer with the track on the inside of the cabinet and guide it into place.





24 GAGE STEEL RTA TOOL CABINET
INSTALL INSTRUCTIONS





DRAWER ASSEMBLY:

1) Bend the two sides of DRAWER BOTTOM **(Y)** upwards to create the side walls.



The Steel Metal Runners should be on the outside of the drawer.



2) Insert the edge of **(Z)** with 3 notches into the back of DRAWER BOTTOM **(Y)** using a mallet to wedge into place. Make sure all the notches at tops and sides of **(Y)** are snapped into notches on **(Z)**.



Below is what it will look like when **Z has fit into the notches along the side and bottom of **Y**.



3. Insert the edge without the ridge of DRAWER PANEL **(W)** at the other side of DRAWER BOTTOM **(Y)**. You may use a mallet to apply force. Note: Drawer bottom must rest on the inside of DRAWER PANEL **(W)**.



4. Insert the SUPPORT PANEL **(X)** at the back of the DRAWER PANEL **(W)**, be sure to insert this with the ridges edge upwards. Bang into place with a mallet. Once it passes the notches, it's locked in.



24 GAGE STEEL RTA BASE CABINET
INSTALL INSTRUCTIONS

NEWAGE PRODUCTS INC.

ASSEMBLY INSTRUCTIONS:

CABINET LEVELING

(for all cabinets except for wall cabinet)

1. Place a small magnetic level onto the top of the cabinet to verify the levelness of the cabinet.
2. If the floor slopes and the cabinet is not level, lift the adjustable sleeve on the leg and adjust the cabinets height-adjustable leveling leg by turning the nut on top of the cabinet's foot, up or down to bring the cabinet to a level position. This may require two people, one person to verify / bring cabinet level and one person to adjust the legs up and down simultaneously.
3. The cabinet must be adjusted front to back and side to side.
4. Do not put items in the cabinet until the leveling process is complete.

MOUNTING OF THE WORKTOP:

(optional, for base cabinets)

NOTE: Base Cabinet Drawers must be removed prior to mounting Worktop.

- Pull each drawer out to full extension, simultaneously depress the left lock up and right lock down in each slider while pulling out the drawer. The drawer will slide out of the tracks ready to remove. See the diagram to note where the locks are on the drawer slides.



1. Place the Worktop on top of both the base cabinet .
2. Align the Worktop so that it is flush with the side of the base cabinet.
3. Using the supplied Worktop hardware fasten screws through the cabinet top into the Worktop. A cordless power drill is required to drive the screws into the Worktop.



4. Put drawers back into base cabinet by aligning them with the ball-bearing slides drawer tracks. The drawer should slide back into place. Push the drawer fully into the cabinet, then pull it out to full extension. If the drawer does not stop at full extension, or feels loose, the drawer has not been put back into the drawer slides properly. Ensure both drawer slides attached to the drawer are running along the drawer slides attached to the frame of the cabinet.

ENABLING LOCKING MECHANISM

1. Locate black vertical locking column attached to back-inside of cabinet; this slides up and down. Push upwards to expose small hole.



2. Locate Locking Rod, and insert the tip of the bent end into hole in locking column at back of cabinet.



3. Locate the locking device at the top-inside of tool cabinet, and locate the thin slit between the locking device. Remove the pin attached to the cabinet lock, and set aside. Do not discard. Using the other end of the Lock Rod with a hole through it, align this with the lock hole.



4. Once holes are aligned, insert the pin through both to lock into place, between lock slit.



5. Test the lock.

Locking device is now ready.

24 GAGE STEEL RTA TOOL CABINET
INSTALL INSTRUCTIONS

MOUNTING CABINETS INTO DRYWALL / STUDDED WALL: WARNING: ALL CABINETS MUST BE MOUNTED TO STUDS BEFORE LOADING THE CABINETS WITH ITEMS

Each locker or base cabinet must be mounted to the wall with at least two of the provided mounting screws. Each wall cabinet must be mounted with four screws.

1. Using a stud finder locate the studs in the wall where the wall cabinet is to be placed.
2. Once studs are located, using a pencil and a level mark a vertical line to indicate stud location.

3. Place the cabinet into position tight against the supporting wall.
4. Open the doors and locate the perforated mounting strip on the top and bottom of the backside of the cabinet.
   Note: the cabinet has a perforated strip of holes at the top and bottom of the cabinet, the locker only has a perforated strip at the top of the cabinet.




5. Align the previously marked stud lines with a perforated hole by shifting the cabinet slightly.
6. Place a small magnetic level on top of the wall cabinet and adjust the orientation of the cabinet to bring it to a level position.



7. Once leveled, using the supplied mounting hardware fasten a 2.5" x ¼" cabinet mounting lag bolt with a large washer through the cabinet and into the stud. This can be done by hand with a 7/16th socket wrench or a cordless power drill with a 7/16th socket attachment. Do not over tighten bolts! Once the fender is sitting tightly flush with the backside of the cabinet stop.
8. Repeat Step 6 three additional times with the remaining mounting hardware to install the wall cabinet. You will only repeat this one more time for the locker, as it only has 2 mounting lag bolts.

WALL AND LOCKER CABINET WALL MOUNTING INTO CONCRETE BLOCK / MASONRY WALL:

NOTE: Masonry Hardware **NOT** Included

REQUIRED HARDWARE:

- 2 ¼" x ¼" Tapcon Concrete Anchor (4)

0r

- #10 x 2" Screw with 3/16" masonry plug (4)

1. Place the wall cabinet into position tight against the supporting wall.
2. Open the doors and locate the perforated mounting strip on the top and bottom of the backside of the cabinet.




3. Place a small magnetic level on top of the wall cabinet and adjust the orientation of the cabinet to bring it to a level position.



4. Using a hammer drill, drill 4 pilot holes through the perforated strip in the backside of the cabinet and through the wall.
5. Using either the 2 ¼" x ¼" Tapcon Concrete Anchor or #10 x 2" Screw with 3/16" masonry plug method and the supplied fender washers fasten the cabinet directly to the wall. This application requires a cordless power dill with a #2 Philips bit for ease of installation.
6. Repeat Step 3 - 4 three additional times with the remaining mounting hardware.

THANK YOU for your purchase!
Please give us a call, or visit us online if you have any other questions or comments.

Give us your feedback for a chance to WIN! Take our quick 2 minute survey and enter for your chance to win something FREE from NEWAGE! Visit the website for details at www.newageproducts.com

NEWAGE PRODUCTS INC.
THE ORGANIZED GARAGE

201 Chrislea Road, Vaughan. ON, Canada
1-877-306-8930
www.NEWAGEPRODUCTS.com

NEWAGE PRODUCTS INC. STEEL CABINETRY WARRANTY
1 YEAR LIMITED MANUFACTURER WARRANTY

For one year from the date of purchase, when this product is installed, operated and maintained according to the instructions attached to or furnished with the product, NewAge Products Inc. will replace the defective product or parts if the part fails as a result of defective materials or workmanship.

NEWAGE PRODUCTS INC. WILL NOT PAY FOR:

1. Service calls to correct the installation of any NewAge products or to instruct you how to use or install them.
2. Damage resulting from improper handling or shipping of products, or products damaged by accident, misuse, abuse, fire, flood, improper installation, acts of God, neglect, corrosion, modification or mishandling.
3. Products damaged by improperly loading beyond the specified maximum weight capacity outlined in the instructions provided with the product.
4. Repairs or replacement when your product is used in other than normal, single-family household use, such as a commercial environment, or handled in any way inconsistent with the installation instructions included with the product.
5. Cosmetic damage, including scratches, dings, dents or cracks in paint that do not affect the structural or functional capability of the product.
6. Surfaces damaged due to chemical interaction resulting in corrosion of paint or metal.
7. Replacement parts for NewAge products outside Canada and the United States.
8. Replacement keys or locking mechanisms.
9. Loss of product contents due to left, fire, flood, accident or acts of God.
10. Shipping or freight fees to deliver replacement products or to return defective products.
11. Any labor costs during the limited warranty period.

DISCLAIMER OF IMPLIED WARRANTIES; LIMITATION OF REMEDIES

IMPLIED WARRANTIES, INCLUDING TO THE EXTENT APPLICABLE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED TO THE EXTENT LEGALLY PERMISSIBLE. ANY IMPLIED WARRANTIES THAT MAY BE IMPOSED BY LAW ARE LIMITED TO ONE YEAR, OR THE SHORTEST PERIOD ALLOWED BY LAW. SOME STATES AND PROVINCES DO NOT ALLOW LIMITATIONS OR EXCLUSIONS ON HOW LONG AN IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS LASTS, SO THE ABOVE LIMITATIONS OR EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE OR PROVINCE TO PROVINCE